PLATOWOOD®

Declaration of Performance

PERFORMANCE DECLARATION Nr. 20250418-01

- 1. Unique identification code of the product type: Platowood Fraké.
- 2. Intended use(s): For interior and/or exterior facade cladding on buildings
- 3. Manufacturer: Platowood BV, Westervoortsedijk 73, 6827 AV, Arnhem, Netherlands
- 4. System(s) of assessment and verification of constancy of performance: AVCP3 and AVCP 4
- 5. Harmonised standard: EN14915:2013
- 6. Declared performance(s):

Intended use:

Density and thickness

Reaction to fire

Release of formaldehyde

PCP content

Release of other dangerous substances

Water vapour permeability

Sound absorption NPD

Thermal conductivity

Resistance to fixings

Biological durability Class

Internal and external

497, 18/8-40/8

D-s1,d0 acc. to EN 13501-1

E1

< 5 × 10 60

NPD

NPD

NPD

0,115 W/m.K

Density pre-drilling advisable

1-2 (use class 1-3)

Appropriate technical documentation and/or specific technical documentation:
 The fire class has been determined by MeKa (NoBo No. T-316) in report K04/2024.
 The durability has been determined by EPH (Entwicklings- und Prüflabor Holztechnologie GmbH) in report 2219008. All data can be found on our website www.platowood.nl.

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mr. Han van Rooijen, Operations Director

In Arnhem on April 29, 2025

Signature